


TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
 DECORATION	<b>COBALT</b>	FT N° 65 version 2

This is a through-coloured PVC wallcovering, printed using water-based inks, on non-woven backing. Washable, impact and scratch resistant, this wallcovering is suitable for intensive use in public buildings. In line with regulations, it has M1, B s2 d0 fire resistance rating. Quick and easy to hang. Simply paste the wall and align the edges of each strip.

### Description

Item code	CBLT 9134... / 9135... / 9139...
Name	COBALT
Range	Decoration
Type	PVC wallcovering
Plain	Yes - 12 colours
Patterned	Yes - 2 patterns / 10 item codes

### Composition

Type	PVC
Backing	Non-woven backing
Weight	380 g/m <sup>2</sup>
Thickness	0.55 mm
Ink	Water-based printing inks

### Regulations - Environment

Fire rating	B s2 d0	Standard EN 13 501 -1
Acoustics	Alpha w = 0,10 or 0,15 according to the substrate / acoustic report: PEUTZ - N°A3151	
Light fastness	>6	Standard EN 259
VOCs	A+	ISO 16000
DoP	DoP-CPR-VIEP-21 / <a href="http://www.texdecor.fr">www.texdecor.fr</a>	Standard EN 15 102
Care	Extra washable	Standard EN 259
Use	Intensive	Standard EN 259

### Packing - Packaging

Size of widths	+/- 0.70m
Length of roll	10.05 M
Partial sale to order	No
Dispenser box	No
Suspended core packaging	No
Box size	3 packages

FSC Certified Cardboard

2 rolls	4 rolls	6 rolls
120*190*750mm	190*210*760mm	230*330*730mm

Weight of a roll 2.31 kg to 2,80 kg

### Hanging

Adhesive	Ovalit TM - Quelyd Murale	MSDS available
Adhesive instructions	Apply to the wall, using a roller	
Quantity of adhesive	+/- 200gr/m <sup>2</sup>	

	CBLT 9134... plain	CBLT 9135... pattern	CBLT 9139... Pattern
Match	free match	Straight match	drop match
Match connection		1,5 cm	45 cm

Seam	Edge to edge
Removal	Pelable